



WOOD

Elegance
Atelier Collection

Product
Datasheet
2015

WOOD

Elegance Atelier Collection



TECHNICAL INFORMATION	ELEGANCE
Thickness	22 mm
Width	280 mm
Length	2520 mm
Wearlayer thickness (mm)	app. 4,0
Weight (kg/m ²)	app. 13
Taber Abraser/Lacquer's wear resistance prEN 13696	
abrasion penetration Proteco Lacq.(revs)	N/A
abrasion penetration Proteco Nat.(revs)	N/A
abrasive wear (mg/100revs)	N/A
<i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i>	
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL_w in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D _{fl}
Thermal insulation value (RT m ² K/W)	
board only	0,152
with rag felt	0,182
with 2 mm Tarkofoam/flex II	0,192
Installation*	Glue down
Underfloor heating compatible**	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

Hardwax Oil Tongue & Groove

ELEGANCE

Plank, 22x2520x280 mm. 4 side minibevel.

- Oak brushed •
- Oak Lime Stone brushed •
- Oak Umber Brown brushed •
- Oak Urban Grey brushed •

* Contact your flooring supplier for further information.

** Not suitable for the woodspecies beech and maple.

Elegance Proteco Hardwax Oil



Wood floors, Brinell Hardness (BHN), EN1534

