



WOOD

Epoque Mini
Classic Collection

Product
Datasheet
2015

WOOD

Epoque Mini Classic Collection



TECHNICAL INFORMATION	EPOQUE MINI
Thickness	14 mm
Width	117 mm
Length	1075/1245 mm
Wearlayer thickness (mm)	app. 3,5
Weight (kg/m ²)	app. 8,0
Taber Abraser/Lacquer's wear resistance* prEN 13696	
abrasion penetration Proteco Lacq.(revs)	>4000
abrasion penetration Proteco Nat.(revs)	>3500
abrasive wear (mg/100revs)	app. 3,5
<i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i>	
Reduction of sound weighted index index "footfall" to the room below.	
NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL_w in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D _R
Thermal insulation value (RT m ² K/W)	
board only	0,101
with rag felt	0,121
with 2 mm Tarkofoam/flex II	0,141
Installation*	Floating /Glue down
Underfloor heating compatible**	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

** Contact your flooring supplier for further information.

*** Not suitable for the woodspecies beech and maple.

EPOQUE MINI	Lacquer 2-lock	Natura 2-lock
Plank, 14x 1075/1245x117 mm. 2 side minibevel.		
Oak Nature	•	•
Oak Nature brushed		•
Oak Rustic brushed		•
Oak White		•
Oak Patina White brushed		•
Oak Cotton White		•
Oak Stone Grey brushed		•
Oak Praline brushed		•
Oak Java Gold brushed		•

Epoque Proteco Lacquer / Proteco Natura



Wood floors, Brinell Hardness (BHN), EN1534

