



WOOD

# Tango

Classic Collection

Product  
Datasheet  
2015

WOOD

# Tango

Classic Collection



TECHNICAL INFORMATION	TANGO
Thickness	13 mm
Width	117/162/190/194 mm
Length	1075/1245/2000/2200/2281 mm
Wearlayer thickness (mm)	app. 2,5
Weight (kg/m <sup>2</sup> )	app. 7,3
Taber Abraser/Lacquer's wear resistance* prEN 13696	
abrasion penetration Proteco Lacq.(revs)	>4000
abrasion penetration Proteco Nat.(revs)	>3500
abrasive wear (mg/100revs)	app. 3,5
<i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i>	
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL <sub>w</sub> in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D <sub>fl</sub>
Thermal insulation value (RT m <sup>2</sup> K/W)	
board only	0,101
with rag felt	0,121
with 2 mm Tarkofoam/flex II	0,141
Installation*	Floating /Glue down
Underfloor heating compatible**	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

\*\* Contact your flooring supplier for further information.

\*\*\* Not suitable for the woodspecies beech and maple.

Tango Proteco Lacquer / Proteco Natura



TANGO MAXI	Natura 2-lock Width: 162 mm	Natura 2-lock Width: 190 mm
<b>Plank, 13x2000/2200 mm. 2 side minibevel.</b>		
Oak Eu Nature	•	•
Oak Eu Rustic brushed		•
Oak Eu Rustic White brushed	•	
Oak Am Antique brushed	•	
Oak Rustic Cotton White		•
Oak Soft Grey brushed	•	
Oak Brown brushed	•	
Ash White brushed	•	
Ash Ivory	•	

TANGO MINI	Natura 2-lock Length: 1075mm	Natura 2-lock Length: 1245mm
<b>Plank, 13x117 mm. 2 side minibevel.</b>		
Oak Nature	•	•
Oak Rhapsody brushed	•	•
Oak White brushed	•	•
Oak Grey brushed	•	•
Oak Cumin		•

TANGO 2-STRIP	Lacquer 2-lock	Natura 2-lock
<b>2-strip, 13x2281x194 mm.</b>		
Oak Nature	•	•
Oak Rustic brushed		•
Oak Cotton White		•
Oak White		•
Oak Stone Grey brushed		•
Oak Light Hazel brushed		•

Wood floors, Brinell Hardness (BHN), EN1534



www.tarkett.com