

WOOD

**Viva**  
Classic Collection

Product  
Datasheet  
2015

WOOD

# Viva

Classic Collection



TECHNICAL INFORMATION	VIVA
Thickness	8,5 mm
Width	110/190 mm
Length	1220 mm
Wearlayer thickness (mm)	app. 0,6
Weight (kg/m <sup>2</sup> )	app. 7,7
Taber Abraser/Lacquer's wear resistance* prEN 13696	
abrasion penetration Proteco Lacq.(revs)	>4000
abrasion penetration Proteco Nat.(revs)	>3500
abrasive wear (mg/100revs)	app. 3,5
<i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i>	
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL <sub>w</sub> in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D <sub>f1</sub>
Thermal insulation value (RT m <sup>2</sup> K/W)	
board only	0,054
with rag felt	0,074
with 2 mm Tarkofoam/flex II	0,094
Installation*	Floating /Glue down
Underfloor heating compatible	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

\* Contact your flooring supplier for further information.

Viva Proteco Lacquer / Proteco Natura



Wood floors, Brinell Hardness (BHN), EN1534



VIVA 3-STRIP	Lacquer Ultraloc	Natura Ultraloc
<b>3-strip, 8,5x1220x190 mm</b>		
Oak	•	•
Oak Praline		•
Maple		•
Maple Nature	•	
Beech Nature	•	
Cherry	•	
Walnut	•	•

VIVA 2-STRIP	Lacquer Ultraloc	Natura Ultraloc
<b>2-strip, 8,5x1220x190 mm</b>		
Oak	•	•
Oak brushed		•
Oak White		•
Ash White		•
Ash Design White	•	
Walnut	•	

VIVA PLANK	Lacquer Ultraloc	Natura Ultraloc
<b>Plank, 8,5x1220x190 mm. 4 side micro bevel.</b>		
Oak	•	•
Oak brushed		•
Oak Brown brushed		•

VIVA LINE	Natura Ultraloc 2 side micro bevel	Natura Ultraloc 4 side micro bevel
<b>Miniplank, 8,5x1220x110 mm.</b>		
Oak		•
Oak brushed		•
Oak Patina White brushed		•
Oak Misty Grey brushed	•	
Oak Denim brushed	•	
Oak Avocado brushed	•	
Oak Black brushed		•
Walnut		•