



COPE WITH SLIGHT UNEVENNESS IN SUBSTRATES

For LVT Click and LVT glued flooring **TARKOFLAT LOOSE-LAY**



SUBFLOOR TYPE

- . Residential and light traffic commercial applications (Class 32 max.)
- . For renovating old ceramic flooring, granite, marble, tiles, wood floors, cement substrates
- . Suitable for temporary installation (events, exhibitions)

COMPATIBLE FLOORING

- ✓ LVT Click and LVT glued flooring (planks or tiles)

DESCRIPTION

Material: calandered PVC foil, loose-lay (naked)

Total weight: 1,500g per m²

Total thickness: 1.0mm

ARTICLE NUMBER

Article code: 3568004 - Grey

Packaging: single roll - 25m x 2m (50m²)


Minimum order: 1 roll - no cutting service available



INSTALLATION


- . [Installation instructions](#) ↗

Ready-to-use solution



- ◆ **Reduces slight unevenness** in older subfloors by up to 1.5mm depth and 3mm width
- ◆ **Prevents telegraphic effect**, the appearance of bumps and ridges from the substrate by up to 1.5mm depth
- ◆ Provides savings of up to 20% **without need for expensive levelling**

Quick and easy to install



- ◆ Rolls out easily for **quick coverage**
- ◆ **Minimises downtime** during installation

Easy to remove and refurbish



- ◆ Avoids damage to substrate thanks to **loose-lay** installation
- ◆ **Simplifies removal** at end of life
- ◆ Allows **easy access to substrate** in case of problem

COORDINATED ACCESSORIES



LVT skirting:

- ◆ rigid PVC for high resistance to impact
- ◆ PUR treatment for easy maintenance
- ◆ matching film for nice finish

Article code: 26640...



WET SUBSTRATE



UNEVEN FLOOR



ACOUSTIC COMFORT



PRESERVED FLOORING



DAMP PROOF



FLOOR PROTECTION



| TARKOFLAT LOOSE-LAY | TARKOFLAT SELF-ADHESIVE |