








# Technical Data Sheet



## Tarkolay Resilient Slip Sheet Membrane

Properties	Standards	Tarkolay Options		
		Resicore Pad and Pour	Omnisports Cushion Backed	Dropzone & Dropzone Speckle
<b>Performance and Installation</b>				
Moisture tolerance	ASTM F1869	15 lbs		
Moisture tolerance	ASTM F2170	96% RH		
Product compatibility		Yes	Yes	Yes
Adhesive required		Multi-Poxy	Multi-Poxy	Multi-Poxy
Compatibility with "in slab" heating systems		Yes *conditions required		
Direction		Parallel and offset with sheet flooring		
<b>Technical Characteristics</b>				
Type		Resilient Sheet		
Composition		Vinyl		
Color		White		
Width	EN 426/427	2 m (6' 6")		
Length	EN 428/429	45 m (147' 7 ")		
Weight	EN 430	0.26 lbs/Sq. Ft.)		
Roll Weight	EN	230 lbs		
Permeance	ASTM E96	< .20 Perm		
Dimensional Stability	EN 434	0.01%		
<b>Dimensions (EN 426/EN 427)</b>  6.5 ft. (2 M)  147' 7" ft (45 M)		<b>Total thickness (EN 428/EN429) :</b>  1.3 mm (0.05")		<b>Total weight (EN 430) :</b>  .26 lb/sq.ft. (1.16 kg/m <sup>2</sup> )

### Key points



#### Description :

Vinyl resilient sheet slip sheet membrane designed to separate the installation system from the effects of vapor pressure at the surface of the slab.

#### Installation :

- Omnisports Cushion Backed
- Dropzone and Resicore Sheet Rubber
- Resicore Pad and Pour

**Surface Texture:** Smooth

**Backing Texture:** Dimpled

#### Compatible Substrates :

Properly constructed concrete, asphalt, and wood substrates. See installation guidelines for more information.

#### Compatible Substrates: Properly constructed and prepared Concrete, Wood, Asphalt, and Cementitious Underlayments

Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information.

We reserve the right to modify these specifications without affecting their compliance with standards. Some results may slightly vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.



**Potential LEED Credits:**  
Tarkett Sports chooses sustainability in concert with performance. Please contact your area representative for assistance.

**TARKETT SPORTS**  
175 N. Industrial Blvd.  
Calhoun, GA 30071  
Tel (888) 364-6541  
Fax (678) 364-6540  
[www.tarkettsportsindoor.com](http://www.tarkettsportsindoor.com)