

**PRODUCT  
DATA SHEET**

# STARFLOOR CLICK 50 Tiles

**Type of flooring**

**ISO 10582**

**Compact Resilient Flooring**

**Class of use**

**ISO 10874**



**23**



**32**

**Class**

## Description



**ISO 24346**  
(EN 428)

**5,00 mm**



**ISO 24340**  
(EN 429)

**0,50 mm**



**ISO 24342**  
(EN 427)

**60,3 cm  
31 cm**



**ISO 23997**  
(EN 430)

**9,2 kg/m<sup>2</sup>**



**EN 660-2**

Abrasion group

**T**  
**≤ 2,00 mm<sup>3</sup>**



**ISO 4918**

(EN 425)  
Castor wheel test

**OK**



**EN ISO 717/2**

Impact sound  
absorption

**5 dB**



**ISO 24343-1**

(EN 433)  
Static indentation

**≤ 0,08 mm**

## Optional Characteristics



**ISO 105/B02**  
Light fastness

**≥ 6**



**EN 1815**

Static electrical  
propensity

**≤ 2 kV**



**Fire Classification**

EN 13501-1

Report N° :

**Bfl-s1**  
**RA13-0130**



**ISO 23999**  
(EN 434)

Dimensional stability

**≤ 2 mm  
< 0,10 %**



**Recyclable**

**OK**



**ISO 24342**

7 Tiles/box  
1,708 m<sup>2</sup>



**ISO 10456**  
(EN 12524)

Thermal resistance  
for underfloor heating

**0,04 m<sup>2</sup> k/W**



**Slip resistance**

EN 13893

DIN 51130

**μ ≥ 0,30  
R9**



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.