

**PRODUCT
DATA SHEET**

Exclusive 280T
Vinyl Collection

December 2014

Type of flooring

EN ISO 26986 **Vinyl Floorcovering**

Class of use

EN ISO 10874



Class

23

32

Description



EN ISO 24346
(Previously EN 428)

2,80 mm



EN ISO 24340
(Previously EN 429)

0,35 mm



EN ISO 24341
(Previously EN 426)

25 m
4+3+2m



EN ISO 23997
(Previously EN 430)

1, 880 kg/m²



EN660-2
Abrasion resistance **≤2mm³**
(Class T according to EN 649)



ISO 4918 **OK**
(EN 425)
Castor wheel test



EN ISO 717/2 **ca. 19 dB**
Impact sound absorption



EN ISO 24343-1 **≤ 0,20 mm**
(Previously EN 433)
Static indentation

Optional Characteristics



ISO 105/B02
Light fastness **≥ 6**



EN ISO 23999 **≤ 0,40 %**
(Previously EN 434)
Dimensional stability



EN ISO 10456 **0,04 m²/kW**
(EN 12524)
Thermal resistance
for underfloor heating



Slip resistance
EN 13893
DIN 51130

μ ≥ 0,30
R10



Recyclable

NO



**Chemical
resistance**

OK



Fire Classification
EN 13501-1 **Cfl-s1**
(glued over wooden panel)
Report N° : **RA10-0252**



EN 1815 **≤ 2 kV**
Static electrical
propensity



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.