

**PRODUCT  
DATA SHEET**

**Exclusive 300**  
Vinyl Collection

December 2014

**Type of flooring**

EN ISO 26986 **Vinyl Floorcovering**

**Class of use**

EN ISO 10874



**23**



**31**

**Description**



**EN ISO 24346**  
(Previously EN 428)

**3,00 mm**



**EN ISO 24340**  
(Previously EN 429)

**0,25 mm**



**EN ISO 24341**  
(Previously EN 426)

**25 m**  
**4+3+2m**



**EN ISO 23997**  
(Previously EN 430)

**1,840 kg/m<sup>2</sup>**



**EN660-2**  
Abrasion resistance **≤2mm<sup>3</sup>**  
(Class T according to EN 649)



**ISO 4918** **NO**  
(EN 425)  
Castor wheel test



**EN ISO 717/2** **ca. 20 dB**  
Impact sound absorption



**EN ISO 24343-1** **≤ 0,35 mm**  
(Previously EN 433)  
Static indentation

**Other Characteristics**



**ISO 105/B02**  
Light fastness **≥ 6**



**Slip resistance**  
EN 13893  
DIN 51130 **μ ≥ 0,30**  
**R10**



**Fire Classification**  
EN 13501-1 **Cfl-s1**  
(glued over wooden panel)  
Report N° : **RA14-0053**



**EN ISO 23999** **≤ 0,40 %**  
(Previously EN 434)  
Dimensional stability



**Recyclable** **OK**



**EN 1815** **≤ 2 kV**  
Static electrical propensity



**EN ISO 10456** **0,05 m<sup>2</sup>/kW**  
(EN 12524)  
Thermal resistance for underfloor heating



**Chemical resistance** **OK**



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.