

# PRODUCT DATA SHEET

# STARFLOOR CLICK 30 Scratched Metal

Type of flooring

ISO 10582

Compact Resilient Flooring

Class of use

ISO 10874



Class

23

31

## Description



**ISO 24346**  
(EN 428)

4,00 mm



**ISO 24340**  
(EN 429)

0,30 mm



**ISO 24342**  
(EN 427)

60,3 cm  
31 cm



**ISO 23997**  
(EN 430)

7,4 kg/m<sup>2</sup>



EN 660-2

**Abrasion group**

T  
≤ 2,00 mm<sup>3</sup>



**ISO 4918**

(EN 425)

Castor wheel test

OK



**EN ISO 717/2**

Impact sound  
absorption

3 dB



**ISO 24343-1**

(EN 433)

Static indentation

≤ 0,08 mm

## Optional Characteristics



**ISO 105/B02**

Light fastness

≥ 6



**EN 1815**

Static electrical  
propensity

≤ 2 kV



**Fire Classification**

EN 13501-1

Report N° :

**Bfl-s1**  
**RA13-0130**



**ISO 23999**

(EN 434)

Dimensional stability

≤ 2 mm  
< 0,10 %



**Recyclable**

OK



**ISO 24342**

9 Tiles/box

1,682 m<sup>2</sup>



**ISO 10456**

(EN 12524)

Thermal resistance  
for underfloor heating

0,03 m<sup>2</sup> k/W



**Slip resistance**

EN 13893

DIN 51130

μ ≥ 0,30  
**R10**



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.