

Omnisports REFERENCE



KEY POINTS

Description :

Vinyl sports floor covering over fibreglass with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

3 types of installation :

- Loose laid (Green Lay)
- Glued Installation
- Installation on Tarkolay

Surface Texture : Sorrent

Compatible Installation :

Association possible with a sub construction (Lumaflex type)

Installation instructions and maintenance guide :

On request

Dimensions (EN 426) :



2 m



20.5 lm or 23 lm

Total thickness (EN 428/EN429) :



6.5 mm (± 0,15mm)

Total weight (EN 430) :



4.71 kg/m² (± 500g)

Technical data in force as from the date of publication (05 /2013).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett. Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Properties	Standards	Omnisports REFERENCE		
		Loose-laid	Glued Installation	Installation on Tarkolay

Technical Characteristics				
Friction	EN 13036-4	88		
Shock absorption	EN 14 808	26 %	27 %	28 %
Vertical deformation	EN 14 809	1.1 mm	1.3 mm	1.3 mm
Vertical ball rebound	EN 12235	100 %	99 %	100 %


Classification		
Reaction to fire	EN 13501-1	Cfl-S1
Hygiene	-	Does not contribute to infection spreading

Technical Characteristics			
Wear Layer	EN 429	0.70 mm	
Resistance to wear	EN ISO 5470-1	0.098 g	
Resistance to indentation	EN 1516	0.21 mm	0.40 mm
Behaviour under a rolling load	EN 1569	0.30 mm	0.40 mm
Resistance to impact	EN 1517	No degradation	

Specific Characteristics		
Surface treatment	Topclean X-treme performance protection	
Maintenance		

COMPATIBLE SLABS: Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3 m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

Omnisports Reference



On loose laid only



	EN 14904 	Manufactured by: Tarkett France 08200 Sedan FRANCE EN 14904 Omnisports Reference

Tarkett France – 2, rue de l'Égalité – 92748 Nanterre cedex – TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com
 S.A.S au capital de 30800000 euros – RCS Nanterre 410 081640
www.tarkett-sports.com



THE ULTIMATE SURFACE EXPERIENCE

31/05/2013